

IN THE CLAIMS:

1. (Currently amended) Motor vehicle (1) with a roof (2) having at least one essentially horizontally extending movable roof part (3) configured to be fully opened and to be fully moved to achieve this full opening, wherein the movable roof part extends from an area adjacent to a windshield frame (4) to a rear roof part (5), wherein the movable roof part (3) is separated from the rear roof part (5), and wherein the movable roof part (3) comprises a front section and a raisable rear section connected to the front section so as to form a continuous structural unit, wherein the rear section is raisable in such a way that the section of the movable roof part (3) located in front of the raisable rear section remains in a closed position and the movable roof part (3) is in a low draft ventilation position that forms an opening between upper edges of side windows of the motor vehicle, and wherein the movable roof part (3) occupies the entire width between the upper edges of the side windows (7) of the motor vehicle (1).

2. (Canceled)

3. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the movement of the raisable rear section into and out of its raised position is possible while the vehicle is traveling.

4. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the movable roof part (3) is covered with a flexible covering (9).

5. (Previously presented) Motor vehicle in accordance with Claim 1, wherein to allow the raisable rear section to be raised, a roof bow (27) is provided which engages under the rear section and is displaceably mounted on lateral frame parts (11) of the movable roof part (3).

6. (Previously presented) Motor vehicle in accordance with Claim 5, wherein at least one remotely controlled drive is provided for the displacement of the roof bow (27).

7. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) is in the same position with the movable roof part (3) completely open and with the

movable roof part (3) completely closed.

8. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) is lowerable below a belt line (31) of the automobile body.

9. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) covers a rigid roll bar (32).

10. (Previously presented) Motor vehicle in accordance with Claim 1, wherein the rear roof part (5) is at least partially movable to create an opening for the passage of the fully movable roof part (3) to allow the latter to be opened.

11. (Previously presented) Motor vehicle in accordance with Claim 10, wherein the rear roof part (5) is swingable open about a rear axis (33) to create an opening for the passage of the roof part (3) and is swingable closed again over the opened roof part (3).

12. (Previously presented) Motor vehicle in accordance with Claim 9, wherein the opening for the passage of the movable roof part (3) is located between the rigid roll bar (32) and the opened rear roof part (5).